



- Specification:
- 1). Driving: Duty:1/240, Bias:1/16,VLCD.23.0V,VDD:5.0V
  - 2). Viewing angle: 6 O'clock
  - 3). Display mode: STN/Negative/Transmissive/BLUE
  - 4). Operating temp.: -20°C~+70°C  
Storage temp.: -30°C~+80°C
  - 5). IC: RA8835 (or compatible)
  - 6). Backlight: EDGE WHITE
  - 7). Dimensions with mark "\*" are important, with mark "()" are referenced
  - 8). All the raw materials are RoHS compliant

J1

PIN	1	2	3	4	5	6	7	8	9	10
CONNECTOR GND	VDD	V0	/MR	RD	CE	A0	RST	DB0	DB1	
PIN	11	12	13	14	15	16	17	18	19	20
CONNECTOR DB2	DB3	DB4	DB5	DB6	DB7	DB7	DB7	DB7	DB7	DB7

J2

PIN	1	2	3	4	5	6	7	8	9	10
CONNECTOR GND	VCC	V0	A0	/MR	RD	DB0	DB1	DB2	DB3	
PIN	11	12	13	14	15	16	17	18	18	18
CONNECTOR DB4	DB5	DB6	DB7	CE	RST	VOUT	BLA			

REV	REVISION RECORD	DATE
A0	First issue	1-14



深圳市三元晶液晶显示科技有限公司  
Shenzhen TCC LCD Hi-Tech Co., Ltd.

MODEL NO. 模组型号	SYM320240C1V13-5C2B1N3R8-B5NF-25	GENERAL TOL: 公差	±0.3
APPROVED BY		PAGE: 1 OF 1 页面	UNIT: mm 单位
CHECKED BY		PROJECTION 三角法	
DRAWING BY			